

HSU/HSU1



- Resistant to kerbing due to a wear resistant rubber compound and a reinforced sidewall.
- Tyre contour with special tread compound and high tread depth ensures long service life and excellent handling.
- High tech design provides extremely quiet and comfortable ride.
- High-value casing provides the best basis for premium retreadability.



HSU

HSU1



Applications:

Urban application
All axle on city buses

⊙ Recommended axle

Technical data and recommended tyre pressures

Article Number	Tyre Sizes	Tread Pattern	Load Speed Index ¹⁾	Ply Rating	TT	TL ²⁾	Speed Index & re-speed (km/h)	Tread Depth	Overall Inflated Diameter (mm)	Overall Inflated Width (mm)	Recomm- ended Rim (Inches)	Min Dual Spacing (mm)	Slot Radius (mm)	Rolling Circum- ference (mm)	Bluffing Radius (mm)	Recomm- ended Tread Liner Width (mm)	Maximum Load @ Inflation ³⁾			
																	Single		Dual	
																	KG	PSI (BAR)	KG	PSI (BAR)
05140120000	11R 22.5	HSU1	148/145J	16	TL	J100	20.3	1050	279	8.25	314	489	3200	500	230	6300	123 (8.5)	11600	123 (8.5)	
05140080000	275/70R 22.5	HSU1	148/145J	16	TL	J100	21.0	961	267	7.50	303	447	2920	700	235	6300	131 (9.0)	11600	131 (9.0)	
05725760000	305/70R 22.5	HSU1	150/148J	16	TL	J100	20.2	1000	297	8.25	334	463	3050	-	-	6700	123 (8.5)	12600	123 (8.5)	
05140180000	275/80R 22.5	HSU	148/145L	16	TL	L120	18.0	1016	282	8.25	318	447	3185	600	240	6500	123 (8.5)	12000	123 (8.5)	
05727060000	295/80R 22.5	HSU	152/148J	16	TL	J100	21.9	1044	290	8.25	326	487	3185	600	326	7100	123 (8.5)	12600	123 (8.5)	
05727960000	12R 22.5	HSU	152/148J	16	TL	J100	14.3	1084	292	8.25	329	489	3200	600	215	7100	123 (8.5)	12600	123 (8.5)	
05140190000	11R 24.5	HSU	149/146L	16	TL	L120	18.0	1050	282	8.25	318	566	3740	-	-	6500	123 (8.5)	12000	123 (8.5)	

Technical data : "No Liability Assumed!" Data acc. to DIN 7805/4, Wdk-Guidelines 134/2, 142/2, 143/14, 143/25

1) Load Index single/twin tyres fitment and Speed Symbol 2) TT = Tube Type, TL = Tubeless 3) For tyres pressures of 8.0 bar and over, use valve slit cover plates

ContiTread is offered in ContiUrban HA 3 treadliners for suitable Continental casings.